



# System Requirements

## Security

- 2048 bit RSA PKI based VPN
- 256 bit symmetric keys using Salsa20 and AES
- Database & memory encrypted with random 256 bit keys

## SDK

- Plugin SDK with samples to get you started
- C like scripting language complete with samples

## Certified Terminals

- Motorola MC35, MC70, MC75, MC9090
- Intermec CN3
- iMate JAMin, JasJAM, JAMA, Ultimate
- HTC P3600i, TyTN, TyTN II, Diamond
- MWG/O2 XDA Flame, ATOM
- HP iPAQ HX Series
- Opticon H19 imager
- ASUS M530W SmartPhone
- TDS Nomad
- Mobile Compia M3

Call for others



## What's in the Box

- Server as self installing executable
- Desktop client as self installing executable
- Device clients in CAB file formats for SmartPhones and Windows Mobile Devices
- Embedded Firebird database
- Programmable SD card installer
- Management console for administration
- Online manuals

## Recommended Server Requirements

- Windows 2003 or 2003 64 bit edition
- 1GB RAM
- 100GB hard drive preferably in RAID mirror configuration
- Pentium 4 3.0GHz or above or AMD Athlon 2.0GHz or above
- One public IPV4 address and one open TCP port

## SDK Requirements

- Visual Studio 2008 Express or above
- Eclipse IDE to edit/debug script language

## Recommended Device Requirements

- Pocket PC 2003, Windows Mobile 5.x or Windows Mobile 6.x
- 2MB free Program Memory
- 2MB Storage Memory
- Data enabled SIM card with GPRS, EDGE, IRxTT, EVDO, 3G, HSPDA, or alternatively, WIFI, WIMAX or Bluetooth WLAN.

## Recommended Client Requirements

- Windows XP, or Windows 2003 including any of the 64 bit editions
- 5MB hard disk
- Internet connection



Wirelessworx - It Just Worx! ● [www.wirelessworx.com.au](http://www.wirelessworx.com.au) ● [sales@wirelessworx.com.au](mailto:sales@wirelessworx.com.au)  
 1/200 Wellington Rd ● Clayton ● VIC 3168 ● Aust ● T: +61 3 9582-7000 ● F: +61 3 9582-7001